

Pro-Line Brilliance Grout Stain

Durable Urethane Acrylic Formula

Packaging: 23 Colors Available in 16 oz. bottles

*** Durable Urethane Acrylic Formula**

*** Seals and Protects**

*** Rejuvenates old grout**

◆**USAGE:** Brilliance Grout Stain is a user friendly, low cost way to give tiles a new look without replacing the tile or re-grouting. With it's easy to use urethane acrylic formula a long lasting stain is attained to rejuvenate and seal sanded and non sanded grout joints. Brilliance Grout Stain provides a "natural" uniform color that is highly resistant to wear, sunlight, water and extreme temperatures. Change or renew the color of grout. Seals and protects grout from stains* and moisture. Extremely durable, with expected wear of up to 15 years. Water based, applies and cleans easily. Use interior or exterior.

◆**SURFACE PREPARATION:** Grout joint must be tested for previously applied sealers by applying a few drops of water to the joint. If water beads, a sealer is present and must be removed before application.

(Contact Sealer Mfg. for correct sealer remover.)

Existing grout joints must be clean, dry and free of dirt and grease. Any neutral based cleaner will work to achieve this (scrub brush may be necessary). To ensure desired results a small test area is advised, follow installation instructions and allow a minimum 2 hours cure time. The stain should be easily removed from the tile, but bonded permanently to the grout joint. If stain is easily removed from the grout joint, allow longer curing time.

◆**APPLICATION:** • Rubber gloves and proper eye wear are recommended. Finish preparatory work before opening container. SHAKE WELL BEFORE USING! Allow at least 7 days curing time for new grout installations before staining. If more than 1 bottle of a single color is to be used, mix the material together in a large container to ensure uniformity in color. Then pour a small amount into a dish or container. Using a bristle or sponge brush, dip into stain and apply coats to the grout using a back and forth motion. Thin, even coats should be applied, limiting the amount of stain that gets on the tile.

Allow stain to dry at least 20 minutes, but not more than 30 minutes (time will vary depending on ambient temperature). After Brilliance Grout Stain has dried on the joint, dampen the area with water and let stand 5 minutes before removing excess grout stain from the surface of the tile using a white nylon scrub pad. (It is recommended to start out by staining only 4 to 6 sq. ft. at a time to get a feel for the stain.) If you are going from a dark to a lighter color, 2 or more applications (coats) of stain may be necessary. Follow the above instructions but, allow a minimum of 2 hours drying time between coats. Ready for surface traffic in 24 hours. Keep area dry for at least 48 hours. Avoid direct scrubbing on grout joints for 20 days to allow stain to reach maximum durability.

◆**NOTE:** use caution when cleaning tiles that may scratch or become damaged from scrubbing. Test for potential tile damage in an inconspicuous area prior to use.

◆**CLEAN UP:** Clean applicator tools with water after each use. Dispose of empty bottles according to state and local regulations. Unused portion of Brilliance Grout Stain should be capped and stored in a cool dry place.

◆**ROUTINE MAINTENANCE:** For routine cleaning of grout, use neutral based cleaners.

◆**APPROXIMATE COVERAGE:** 16 oz. Bottle

4" X 4" tile ¼" joint 140 square feet

12" X 12" tile ¼" joint 250 square feet

18" X 18" tile ¼" joint 330 square feet

◆**NOTE:** Coverage's shown are given for estimating purposes only. Actual job-site coverage's may vary depending on the joint size and application procedures.

◆**CAUTION:** KEEP OUT OF REACH OF CHILDREN

IF INGESTED: Seek medical attention.

EYE & SKIN CONTACT: Flush thoroughly with water. If irritation occurs, seek medical attention.

◆ **LIMITATIONS:** Not recommended for use under water.

Use in temperatures between 45° F and 90° F (4° C and 30° C). Porous tiles may require sealing to ensure that the stain is not absorbed into the tile. Do not use solvent based cleaners to clean stained grout joints. In exterior applications, fading may occur. Exact match to Portland cement grouts may vary due to differences in manufacturing and the nature of Portland cement. Keep from freezing.

* Contact Bonded for stain resistance test results.

◆**Warranty:** Bonded Materials Company ("Bonded Materials") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Bonded Materials sole liability under this warranty shall be limited to the replacement of the product. The statements, recommendations, and technical information provided are furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate. Bonded Materials makes no warranty for a particular purpose with respect to product sold herein, except quality of components shall be in accordance with Bonded Materials standards. It is expressly understood and agreed that the buyer's sole and exclusive remedy shall be replacement of defective products. Handling and actual use of product are beyond the control of Bonded Materials, therefore, no warranty is made, expressed or implied, as to the results obtained from use of the product or against any claims for infringement of patents resulting from the use of the product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Bonded Materials printed instructions. Bonded Materials makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state.

. Data Sheets are subject to change without notice. For latest revision, check our website at www.bondedmaterials.com.
If an installation or materials should be changed outside the detailed instructions, please contact our technical support dept. for assistance.

◆ Bonded Materials Company ◆

4330 N. 43rd Ave. Suite B-4 Phoenix, Az.85031

Ph. 623-873-0001 Toll Free 877-726-6333 www.bondedmaterials.com



rev. Feb-10